



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS
 2. THIN GOLD OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 3. BERYLLIUM COPPER
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 5. TEFLON



RoHS COMPLIANT

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	6/1	ISSUE	A				
6	INSULATOR	NOTE 5	NATURAL	1	100-SMAF-3-50T	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	PART NO.			<h1>G.L.I.</h1>			
5	CONTACT PIN	NOTE 3	NOTE 4	1	100-SMAF-MMCXM-5		APPROVED	<i>Golden</i>	DATE		08-26-'14	TITLE	SMA JACK TO MMCX PLUG ADAPTOR
4	INSULATOR	NOTE 5	NATURAL	1	100-MMCXM-4-50T		CHECKED	<i>Golden</i>	DATE		08-26-'14	DRAWING NO.	100-SMAF-MMCXM-50
3	BODY	NOTE 1	NOTE 2	1	100-MMCXM-3		DRAWN	<i>Angela</i>	DATE		08-26-'14	FILE NO.	R:\D\G\DWG\100\SMAF-MMCXM\50
2	RETAINER RING	NOTE 3	NOTE 2	1	200-1000-5								
1	HOUSING	NOTE 1	NOTE 2	1	100-SMAF-SMBM-1								