



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS
2. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
3. PHOSPHOR BRONZE
4. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
5. TEFLON

1. CRIMPED FERRULE  
HEX CRIMP SIZE .128"
2. CRIMPED CONTACT PIN  
SQ. CRIMP SIZE 0.7mm

RoHS COMPLIANT

11	HEX NUT	NOTE 1	NOTE 2	1	HN-19-5824-31
10	LOCK WASHER	NOTE 1	NOTE 2	1	LW-16-19-06
9	GASKET	RUBBER	RED	1	GS-155-185-15
8	FERRULE	NOTE 1	NOTE 2	1	FR-32-39-95
7	CONTACT PIN	NOTE 1	NOTE 4	1	PIN-06-095-55
6	GASKET	NBR	BLACK	1	GS-90-110-10
5	INSULATOR	NOTE 5	NATURAL	1	5824-6421G1-5-50T
4	CONTACT PIN	NOTE 3	NOTE 4	1	5824-6421G1-4
3	BARREL	NOTE 1	NOTE 2	1	5824-6321G1-3-02
2	INSULATOR	NOTE 5	NATURAL	1	5824-6421G1-2T
1	BODY	NOTE 1	NOTE 2	1	5824-6321G1-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	
SCALE	2/1	ISSUE	1

PART NO.	
APPROVED	DATE 02-02-'18
CHECKED	DATE 02-02-'18
DRAWN ANGELA	DATE 02-02-'18

G.L.I.	
TITLE	N FRONT BULKHEAD CRIMP JACK (FOR RG-174, 188A, 316, LMR100)
DRAWING NO.	5824-6321G1-02-50
FILE NO.	R:\D\G\DWG\5824\6321G1\02\50