



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS
 2. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
 4. TEFLON

RECOMMENDED
 CABLE STRIPPING DIM'S
 (建議剝線尺寸)

1. CRIMPED FERRULE
HEX CRIMP SIZE .213"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A	
5	FERRULE	COPPER	NOTE 2	1	FR-533-648-127C	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				
4	CONTACT PIN	NOTE 1	NOTE 3	1	600-1121A1-4-1.1					
3	INSULATOR	NOTE 4	NATURAL	1	600-1121A1-3-50T					
2	BODY	NOTE 1	NOTE 2	1	600-1121A1-2-06					
1	SHELL	NOTE 1	NOTE 2	1	600-1121A1-1					
						PART NO.		G.L.I. TITLE UHF CRIMP PLUG (FOR RG-58, 58A, 58C, 141 CABLE) DRAWING NO. 600-1121A1-06-50 FILE NO. R:\D\G\DWG\600\1121A1\06\50		
						APPROVED	DATE			07-11-'13
						CHECKED	DATE			07-11-'13
						DRAWN	DATE			07-11-'13